



# Development and Optimization of Multi-Functional SCR-DPF Aftertreatment for Heavy-Duty NOx and Soot Emission Reduction

This presentation does not contain  
any proprietary, confidential,  
or otherwise restricted information

KENNETH RAPPÉ, BO PENG, YONG WANG, FENG GAO,  
JANOS SZANYI

Pacific Northwest National Laboratory

2018 Annual Merit Review, DOE Vehicle Technologies Office

Arlington, VA

June 20, 2018

Project ID: ACS119

## Timeline

- ▶ 4-yr CRADA
  - Start date – July 2016
  - End date – June 2020
- ▶ 41.7% complete

## Budget

- ▶ Contract value – \$2.7M
  - \$1.35M DOE share
  - \$1.35M PACCAR share
- ▶ Funding received
  - FY16 – \$200K
  - FY17 – \$355K
  - FY18 – \$175K

## Barriers

- ▶ **B. Lack of cost-effective emission control** for meeting EPA standards for NOx & PM
- ▶ **E. Durability** of the emission control system: 435,000 miles
- ▶ **G. Cost** of emission control devices ... for heavy duty engines in particular

## Partners



- CRADA partner

# Relevance


## Multi-Functional Aftertreatment: SCR-on-DPF






Pacific Northwest  
NATIONAL LABORATORY

Proudly Operated by **Battelle** Since 1965

### Current 2017 HD Aftertreatment



### Future Advanced Aftertreatment



**Soot trapped upstream**

**Molecular diffusion to washcoat**

► Highly promising strategy of integration

■ Reduced total thermal mass of aftertreatment system

● Faster warm up

● Reduced cold start emissions

■ Improved performance & increased flexibility

● SCR closely coupled to engine

● Increased SCR volume

### ► Challenges to deployment

#### 1. SCR catalyst performance – light/heavy duty

- ❑ Enablers – ultra-high porosity filter development, advanced imaging techniques

#### 2. SCR catalyst durability – light/heavy duty

- ❑ Enablers – small-pore Cu-zeolites, e.g., Cu/SSZ-13. more thermally durable

#### 3. Passive soot oxidation performance (via NO<sub>2</sub>) – heavy duty

- ❑ Economically attractive to manage soot passively for heavy duty
- ❑ With incorporation of SCR phase, competition for NO<sub>2</sub>

*Fast-SCR*



*versus*

*Passive soot  
oxidation*



Dominates NO<sub>2</sub> consumption



Significantly compromises soot oxidation

# Approach

## Modify the SCR catalyst to generate $\text{NO}_2$ in situ

- ▶ Focus – Incorporating increased NO oxidation (to  $\text{NO}_2$ ) through inclusion of a metal-oxide component for selective catalytic oxidation (SCO)
  - i.e. forming an SCR-SCO binary catalyst system (as a single active phase)

## PROJECT OBJECTIVES

- ▶ **NO oxidation**
  - Target: increased NO oxidation to  $\text{NO}_2$
  - ... that then drives increased passive soot oxidation
- ▶ **SCR catalyst performance [i.e.,  $\text{NO}_x$  reduction efficiency (NRE) ]**
  - Target: NO oxidation without oxidizing  $\text{NH}_3$
  - Target: NRE  $\geq$  current state-of-the-art (Cu-CHA)
- ▶ **SCR catalyst durability**
  - Target: durability  $\geq$  current state-of-the-art (Cu-CHA)

Must develop in integrated fashion



# Approach

Modify the SCR catalyst to generate  $\text{NO}_2$  in situ

- ▶ Focus – Incorporating increased NO oxidation (to  $\text{NO}_2$ ) through inclusion of a metal-oxide component for selective catalytic oxidation (SCO)

## PROJECT OBJECTIVES this past year

- ▶ NO oxidation – PACCAR focus
- ▶ SCR catalyst performance and durability – PNNL focus

### ■ Step 1 – SCO substrate

- SCO is envisioned as a  $\text{ZrO}_2$ -based catalyst
- Understanding the impact of  $\text{ZrO}_2$  in close proximity to the SCR catalyst
- ... including the impact on both SCR performance and durability

### ■ Step 2 – SCO catalyst

- Impact of hetero-atoms included with  $\text{ZrO}_2$ 
  - ◆ Inside the lattice structure, outside the lattice structure, etc.
- Including their impact on SCR performance and durability

# Approach



## Schedule and Milestones

Date*	Milestone and Go/No-Go Decisions	Status
November 2017	<u>Milestone:</u> 1 <sup>st</sup> group of optimized SCRF samples with candidate SCO/SCR binary catalyst ready for detailed testing	Complete
February 2018	<u>Go/No-Go decision:</u> Identify candidate SCO/SCR binary phase catalyst with improved soot oxidation performance with competing SCR	Delayed
February 2018	<u>Milestone:</u> Composition for first increased scale testing	Complete (PACCAR)
May 2018	<u>Milestone:</u> 2 <sup>nd</sup> group of optimized SCRF samples with candidate SCO/SCR binary catalyst ready for detailed testing	On-track
August 2018	<u>Milestone:</u> SCRF single wall model complete (without aging behavior)	In pursuit
August 2018	<u>Milestone:</u> Production of catalyst for first increased scale testing	Complete

# Accomplishments

## SCR catalyst performance and durability

- ▶  $\text{ZrO}_2$ -based metal-oxide SCO catalyst
  - Focus – Understanding the impact of  $\text{ZrO}_2$  on SCR performance and durability
  - Baseline – Cu-CHA (Si/Al = 12, Cu ~2.3 wt%, IE level ~30%)
- ▶  ***$\text{ZrO}_2$  addition leads to significantly improved high temperature selectivity by mitigating  $\text{NH}_3$  oxidation***










# Accomplishments

## SCR catalyst performance and durability

- ▶  $\text{ZrO}_2$ -based metal-oxide SCO catalyst
  - Focus – Understanding the impact of  $\text{ZrO}_2$
- ▶ *Identified the generation of a new species resulting from the interaction between extra-framework Cu (i.e., CuO) and  $\text{ZrO}_2$*
- ▶ *Closer vicinity = Increased interaction between extra-framework Cu and  $\text{ZrO}_2$*

TPR




# Accomplishments


## SCR catalyst performance and durability

- ▶  $\text{ZrO}_2$ -based metal-oxide SCO catalyst
- ▶  $\text{ZrO}_2$  addition and extra-framework Cu-incorporation as hetero-atom
- ▶ **Demonstrates the ability to incorporate hetero-atoms into the  $\text{ZrO}_2$  matrix (e.g., for improving NO oxidation) while mitigating  $\text{NH}_3$  oxidation and the adverse impact on SCR performance, and improved durability**

**$\text{NH}_3$  oxidation conditions, i.e., with  $\text{NH}_3$  & without NO**



XRD



- ▶  $\text{CuO}_x \rightarrow$  inferior high-T selectivity
- and**
- ▶  $\text{CuO}_x \rightarrow$  damages the zeolite

i.e. the worm in apple



# Accomplishments

## Taking advantage of a NOx storage component




Pacific Northwest  
NATIONAL LABORATORY

Proudly Operated by **Battelle** Since 1965




- ▶ Including Ba – 90% Cu-CHA + 10% Ba/Zr-oxide

- ▶ With Ba, resolving ...

- Analogous NO oxidation activity
- Increased NOx reduction efficiency




***Ba/Zr-oxide shows evidence of the ability to take advantage of a surface-active species***



# Accomplishments



## Implications of Ba on SCR catalyst durability

- ▶ Including Ba – 90% Cu-CHA + 10% Ba/Zr-oxide
- ▶ **Work has uncovered an aging mechanism that uniquely affects low-temperature activity of BaO/ZrO<sub>2</sub> versus Cu-CHA or with ZrO<sub>2</sub>**



### Low Temperature

- Reduced activity observed



### High Temperature

- Activity compared to ZrO<sub>2</sub>

# Accomplishments




## SCR catalyst durability

- ▶ Including Ba – 90% Cu-CHA + 10% Ba/Zr-oxide
- ▶ Thermally-induced ion-exchange aging mechanism
  - = *function* (time, temperature, proximity)

Ion-exchange aging behavior ...

- 800°C/16-hrs >> 650°C/100-hrs
- Closer vicinity >> physical mixture

**Must be cognizant of aging mechanism  
in relation to SCO catalyst chemistry  
AND proximity to SCR phase**




# Responses to Previous Years Reviewers' Comments

- ▶ The reviewer opined that work on ZSM-5 is a waste of time. This reviewer affirmed that moving to SSZ-13 is correct. The reviewer further remarked that the most important part of the project is the durability study, and S effects need to be included.
  - *We agree that durability must be intimately considered in the development. Thus, this has been PNNL emphasis in the past year*
- ▶ This reviewer commented that the approach seems naive. This reviewer stated that it will be extremely difficult, if not impossible, to balance high SCR conversion with high soot oxidation.
  - *With current state-of-the-art SCR technology, we do not disagree. Thus, we are trying modify current SCR technology to enable the application. This is the novelty of the work.*
- ▶ The reviewer said that work with Cu-ZSM-5 was not relevant. The reviewer noted that it is unclear how the filters are being coated.
  - *ZSM-5 was employed solely as a model system, and we have moved past this stage.*
  - *Filters are being coated by PACCAR*



# Collaboration and Coordination





# Remaining Challenges and Barriers

## ▶ NO oxidation

- Increased NO oxidation to NO<sub>2</sub>
- ... to drive increased passive soot oxidation

## ▶ NOx reduction efficiency (NRE)

- Increasing NO oxidation without oxidizing NH<sub>3</sub>



# Proposed Future Work

## ▶ **NO oxidation**

- Modifying  $\text{ZrO}_2$  chemistry (increased redox, acidity)
- More aggressive active NO oxidation component (e.g., Mn, Co, ...)
- ... with and without Ba

## ▶ **NO<sub>x</sub> reduction efficiency (NRE)**

- Incorporating (Mn, Co, ...) into  $\text{ZrO}_2$ -based lattice
- Prior work – metals in a support lattice structure (i.e., co-precipitated) can be just as active for NO oxidation versus supported
- Leveraging this with the ability of  $\text{ZrO}_2$  to mitigate  $\text{NH}_3$  oxidation activity of hetero-atoms (as shown from extra-framework Cu interaction)

Any proposed future work is subject to change based on funding levels

- ▶  $\text{ZrO}_2$  addition shown to improve performance by interacting with extra-framework Cu (i.e., CuO) and  $\text{ZrO}_2$ 
  - Generation of a new species resulting from the interaction
  - Significantly improved high temperature selectivity by mitigating  $\text{NH}_3$  oxidation
  - Closer vicinity = Increased interaction between extra-framework Cu and  $\text{ZrO}_2$
- ▶  $\text{ZrO}_2$  demonstrates the ability to incorporate hetero-atoms into matrix (e.g., for improving NO oxidation) while mitigating detrimental SCR impact
- ▶ Ba/Zr-oxide shows evidence of the ability to take advantage of a surface-active species as a pathway to enhanced NO oxidation behavior
- ▶ Uncovered an ion-exchange (IE) aging mechanism that uniquely affects low-temperature activity of BaO/ $\text{ZrO}_2$  versus Cu-CHA or with  $\text{ZrO}_2$
- ▶ Development must be cognizant of IE aging mechanism in relation to SCO catalyst chemistry AND proximity to SCR phase



**Pacific Northwest**  
NATIONAL LABORATORY

*Proudly Operated by **Battelle** Since 1965*

# Technical Backup Slides

KENNETH RAPPÉ, BO PENG, YONG WANG, FENG GAO,  
JANOS SZANYI

Pacific Northwest National Laboratory

2018 Annual Merit Review, DOE Vehicle Technologies Office

Arlington, VA







June 20, 2018

Project ID: ACS119



# Backup – Enhancing the Cu/ZrO<sub>2</sub> interaction



- ▶ New species observed in the TPR profile of deposited- and impregnated-ZrO<sub>2</sub> on Cu-CHA







# Backup – Reduced $\text{NH}_3$ oxidation (by $\text{O}_2$ )



Conditions: 360 ppm  $\text{NH}_3$ , 14%  $\text{O}_2$ , 2.5%  $\text{H}_2\text{O}$ , balanced by  $\text{N}_2$ , total flow rate 300 mL min<sup>-1</sup>, 120 mg catalyst.

- ▶ Extra-framework Cu is predominantly responsible for the high temperature (400° C+)  $\text{NH}_3$  oxidation activity.
- ▶  *$\text{NH}_3$  oxidation directly affected by the generation of a new species resulting from the interaction between extra-framework Cu and  $\text{ZrO}_2$ .*



# Backup – (S)TEM-EDS observed Cu-enrichment of $\text{ZrO}_2$











Pacific Northwest  
NATIONAL LABORATORY

*Providing Operational Excellence Since 1965*

## ▶ Cu-CHA + $\text{ZrO}_2$ (deposited)


## ▶ Cu-CHA + $\text{ZrO}_2$ (impregnated)




# Backup – Model system study

- ▶ Intent of model catalyst is to mimic the interaction between extra-framework Cu (responsible for enhanced high temperature  $\text{NH}_3$  oxidation) and  $\text{ZrO}_2$ . Inert  $\text{SiO}_2$  is used as an inert substitute for Cu-CHA.

Catalyst 1: Cu impregnated on  $\text{ZrO}_2$ , then physical mixed with  $\text{SiO}_2$



Catalyst 2: Cu and  $\text{ZrO}_2$  simultaneously impregnated on  $\text{SiO}_2$



Conditions: 360 ppm  $\text{NH}_3$ , 14%  $\text{O}_2$ , 2.5%  $\text{H}_2\text{O}$ , balanced by  $\text{N}_2$ , total flow rate 300  $\text{mL min}^{-1}$ , 120 mg catalyst.

- ▶ A close vicinity between Cu and  $\text{ZrO}_2$  is necessary for reduced  $\text{NH}_3$  oxidation activity and inducing the interaction between extra-framework Cu and  $\text{ZrO}_2$ .

# Backup – Understanding BaO/ZrO<sub>2</sub> aging




Pacific Northwest  
NATIONAL LABORATORY

Provided by Battelle Since 1965

- ▶ Aged – 800°C/16 hours
- ▶ Comparing to aging at 650°C/100-hrs
  - Significantly different at low temperature
  - Very similar at high temperature

**Confirms aging mechanism is unique,  
and NOT simply a propagation of  
conventional Cu-CHA aging**



- ▶ 90% SCR + 10% Ba/Zr oxide

